

## Interior / Exterior Vinyl-Acrylic Flat Finish Architectural Coating - Premium

### Description

Duraglide is a premium vinyl-acrylic exterior and interior flat. This product has excellent touch-up, outstanding hide and good washability characteristics. Duraglide offers good color retention & adhesion and is designed for use on all interior drywall and exterior / interior masonry surfaces.

#### Recommended Uses

Properly primed drywall, concrete, masonry, stucco, plaster and metal. NOT recommended for use on exterior wood.

#### Colors

White and stock colors. Custom colors to order. Bases: White, P, D and H

# Packaging

Quart, one and five gallon containers

### Finish

Flat, sheen @  $85^{\circ} = 1.8 - 2.2\%$ 

# Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

#### Primer

Drywall (New): 1100 Hi Build Sealer Drywall (Existing): 4000 Uniprime I Concrete / Masonry: 4600 Uniprime II Metal Non-Galvanized: 8600 Polytec Primer 9600 Protec Metal Primer

Metal Galvanized: 8600 Polytec Primer

4800 Metal Pro Primer

Aluminum: 8600 Polytec Primer

# Application

Brush, roll or spray. Ambient and surface temperatures must be above 40F and relative humidity below 80%. Do not apply when air or surface temperature may drop below 35F within 48 hours.

# **Drvina Time**

Touch: 1 hour Recoat: 4 hours

## Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 3.8Drv = 1.6

## Thinning

Use at package consistency. If thinning is required, use water sparingly.

#### Composition

TOTAL PIGMENT	46.4%
Extenders	31.1%
Titanium Dioxide	15.3%

Vinyl Acrylic Resin 13.8% Additives 4.6% Water 35.2% **TOTAL VEHICLE** 53.6%

Weights & Measurements +/-3.0%

Solids by Volume: 41.8% Solids by Weight: 58.7% VOC: 47 g/l Weight Per Gal: 11.8 lbs. Viscosity: 98 - 102 KU

### Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

CDPH Section 01350 - Standard Method V1.2 2017 **MPI** - #53



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.