

### Exterior 100% Acrylic Matte Flat Finish Architectural Coating - Premium Plus

#### Description

Duratone is a premium plus 100% acrylic matte flat finish for exterior use. This product provides a tough flexible film with outstanding resistance to fading, chalking, alkali burnout & surfactant leaching. Duratone exhibits excellent color retention, hide, adhesion & superior mildew resistance.

#### Recommended Uses

Properly primed wood, stucco, concrete, masonry and properly primed metal.

#### Colors

White, stock colors and custom colors to order.  
Bases: White, A, D, H, & P

#### Packaging

Quart, one and five gallon containers

#### Finish

Flat, sheen @ 85° = 4.1 – 4.7%

#### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming. Woods prone to extractive bleeding, such as cedar and redwood require a stain blocking primer.

#### Primer

Concrete / Masonry:	4600 Uniprime II 8000 Carefree Prime-ZALL
Wood (Exterior):	4200 Terminator II 8000 Carefree Prime-ZALL 8600 Polytec Primer
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Primer
Metal Galvanized:	8600 Polytec Primer 4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

#### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### Drying Time

Touch: 1 hour  
Recoat: 4 hours

#### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

#### Mil Thickness

Wet = 3.7                      Dry = 1.6

#### Thinning

Use at package consistency. DO NOT THIN!

#### Composition

Titanium Dioxide	13.8%
Extenders	22.0%
<b>TOTAL PIGMENT</b>	<b>35.7%</b>
Acrylic Resin	20.0%
Additives	2.1%
Water	42.1%
<b>TOTAL VEHICLE</b>	<b>64.2%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	43.0%
Solids by Weight:	56.2%
VOC:	45 g/l
Weight Per Gal:	11.0 lbs.
Viscosity:	94 - 98 KU

#### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.  
**MPI** - #16



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

04.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

