

340

Zero* V.O.C Interior Latex Semi-Gloss Architectural Coating - Quality

Description

V-PRO 300 (340 Semi-Gloss) is a zero* VOC, interior professional grade latex semi-gloss for use on properly primed walls and ceilings including masonry, plaster, concrete, acoustic, wood and metal surfaces. This product also offers good washability and minimizes wall imperfections.

Recommended Uses

Designed for the repaint maintenance and housing residential markets where a low sheen finish is desired. NOT recommended for horizontal surfaces such as shelves and paneling.

Colors

Tintable White

Packaging

Five gallon containers

<u>Finish</u>

Semi-Gloss, sheen @ 60° = 35.0 - 45.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

<u>Primer</u>

Masonry / Concrete: V-PRO 301 Primer Drywall (New): V-PRO 301 Primer

Drywall (Existing): 4000 Uniprime

8000 Carefree Prime-ZALL

Wood: 4000 Uniprime

8000 Carefree Prime-ZALL

Metal: 9600 Protec Metal Prime

Glossy Surfaces: 4000 Uniprime

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

Drying Time

Touch: 2 hours Recoat: 4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.0 Dry = 1.3

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

TOTAL PIGMENT	24.0%
Extenders	6.1%
Titanium Dioxide	17.9%

 Vinyl Acrylic
 19.4%

 Additives
 6.4%

 Water
 50.2%

 TOTAL VEHICLE
 76.0%

Weights & Measurements +/-3.0%

Solids by Volume: 30.4%
Solids by Weight: 41.4%
VOC: <2 g/l
Weight Per Gal: 9.9 lbs.
Viscosity: 96 - 102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties are hereby disclaimed and excluded including all implied warranties of the nereby disclaimed and excluded including all implied warranties of the suit ability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.