

Description

A quality ready-to-use vinyl flat for interior use on commercial and residential construction. Breezewall provides a washable matte flat film with good touch-up characteristics and outstanding hide.

Recommended Uses

New drywall, interior primed concrete and masonry surfaces.

Colors

White and custom pastel colors to order

Packaging

Five gallon containers

Finish

Flat, sheen @ 85° = 1.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall:	4600 Uniprime II 1100 Hi-Build PVA Sealer
Plaster / Concrete / Masonry:	4600 Unprime II

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch:	1 hour
Recoat:	2 hours

Coverage

Up to 200 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness (Drywall)

Wet = 10.0 - 12.0	Dry = 3.0 - 4.0
-------------------	-----------------

Thinning

DO NOT THIN.

Composition

Titanium Dioxide	7.8%
Extenders	30.7%
TOTAL PIGMENT	38.5%
Vinyl Acrylic Resin	8.6%
Additives	1.6%
Water	51.3%
TOTAL VEHICLE	61.5%

Weights & Measurements +/-3.0%

Solids by Volume:	31.2%
Solids by Weight:	47.1%
VOC:	30 g/l
Weight Per Gal:	11.1 lbs.
Viscosity:	97 - 103 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

LEED - complies with and LEEDv4

CDPH Section 01350 - Standard Method V1.2 2017



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.