

Interior / Exterior 100% Acrylic Primer Architectural Coating - Premium Plus

Description

A premium plus, multi-purpose 100% acrylic primer for exterior and interior applications. Superior resistance to efflorescence and alkalinity on concrete and masonry. Dries to a durable film which provides an excellent base for all top coats.

Recommended Uses

New concrete, drywall, masonry, wood, galvanized metal and aluminum. This product can also be used on most previously painted surfaces.

Packaging

Quart, one and five gallon containers

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming. Woods prone to extractive bleeding require a stain blocking primer.

Passivation coatings applied to galvanized metal must be removed prior to priming. Newly galvanized substrates should be tested for chromates. Refer to SSPC SP-16 for proper testing and surface preparation.

<u>Application</u>

Brush, roll or spray. Ambient and surface temperatures must be above 40F and relative humidity below 80%. Do not apply when air or surface temperature may drop below 35F within 48 hours.

<u>Drying Time</u>

Touch: 30 minutes Recoat: 2 - 4 hours

Coverage

Up to 450 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.0 Dry = 1.8

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

TOTAL PIGMENT	29.2%
Extenders	17.4%
Titanium Dioxide	11.8%

TOTAL VEHICLE	70.8%
Water	44.6%
Additives	4.1%
Proprietary Resin	22.1%

Weights & Measurements +/-3.0%

Solids by Volume: 39.0)%
Solids by Weight: 53.6	3%
VOC: 48 (g/l
Weight Per Gal: 10.9	blbs.
Viscosity: 92 -	- 96 Kl

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

LEED - complies with LEEDv4

CDPH Section 01350 - Standard Method V1.2 2017 MPI - #6



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties are hereby disclaimed and excluded including all implied warranties of the nereby disclaimed and excluded including all implied warranties of the suit ability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.